

TYPE YCP-L

Compression Cable Pulling Heads

Before using this product, it is required to read, understand, and comply with the Safety Operation Maintenance & Installation manual provided with the product.

Features & Benefits

- Range-taking; only 6 compression pulling heads are required to pull #1 AWG through 1000 kcmil wire
- Accommodates:
 - Copper Class B (Concentric, Compressed, Compact) or Class C wire
 - Aluminum Class B (Concentric, Compressed, Compact)
- Easy to install with the 644 Series of dieless installation tools (PAT644 or Y644)
- Parallel installation; each of the 6 compression pulling heads come in 5 unique lanyard lengths for staggering when pulling multiple wire
- Knurl crimp bands clearly indicate the crimp zone locations on the compression pulling head barrels



PAT644 Shown

Catalog Number	Barrel OD (in)	Wire Size (Cu & AL)	Copper Max. Rated Pull Load/ Cable (lbs)	Aluminum Max. Rated Pull Load/ Cable (lbs)	Lanyard Length (in)	Minimum Wire Strip Length (in)	Installation Tooling (# of Crimps)
YPC25L13	.51"	#1 - 1/0 AWG	1,200	400	13"	2.50"	PAT644 (1) Y644 (1)
YPC25L20					20"		
YPC25L27					27"		
YPC25L34					34"		
YPC25L41					41"		
YPC28L13	.69"	2/0 AWG 3/0 AWG 4/0 AWG	1,200 2,000 2,000	400 750 1,000	13"	3.00"	PAT644 (2) Y644 (2)
YPC28L20					20"		
YPC28L27					27"		
YPC28L34					34"		
YPC28L41					41"		
YPC31L13	.88"	250 kcmil 300 kcmil 350 kcmil	2,000 4,000 4,000	1,200 1,500 1,800	13"	3.25"	PAT644 (3) Y644 (3)
YPC31L20					20"		
YPC31L27					27"		
YPC31L34					34"		
YPC31L41					41"		
YPC34L13	1.06"	400 kcmil 450 kcmil 500 kcmil	4,000 5,000 5,000	2,000 2,400 2,700	13"	3.25"	PAT644 (3) Y644 (3)
YPC34L20					20"		
YPC34L27					27"		
YPC34L34					34"		
YPC34L41					41"		

TYPE YCP-L

Compression Cable Pulling Heads
 (Continued)



Catalog Number	Barrel OD (in)	Wire Size (Cu & AL)	Copper Max. Rated Pull Load/ Cable (lbs)	Aluminum Max. Rated Pull Load/ Cable (lbs)	Lanyard Length (in)	Minimum Wire Strip Length (in)	Installation Tooling (# of Crimps)
YPC39L13	1.30"	550 kcmil 600 kcmil 650 kcmil 700 kcmil 750 kcmil	5,000	3,000 3,200 3,600 3,600 3,600	13"	3.25"	PAT644 (3) Y644 (3)
YPC39L20					20"		
YPC39L27					27"		
YPC39L34					34"		
YPC39L41					41"		
YPC44L13	1.50"	800 kcmil 900 kcmil 1000 kcmil	5,000	3,600 3,600 5,000	13"	3.25"	PAT644 (3) Y644 (3)
YPC44L20					20"		
YPC44L27					27"		
YPC44L34					34"		
YPC44L41					41"		



PAT644 Shown